



Armação negativa das lajes do pavimento Térreo (Eixo Y)






Nome


hb bx by


Armação positiva das lajes do pavimento Térreo (Eixo Y)



Planta de vigotas pré-moldadas

Forma do pavimento Térreo (Nível 230)





2 N13 ø12.5 C=615 (1c)

15 x 35

83 N1 c/6

4 N6 Ø8.0 c/20 C=315 (2Ø2c+2Ø3c)

2 N7 ø8.0 C=543 (1c)

2 N13 ø12.5 C=615 (1c)

15 x 35

83 N1 c/6

4 N6 ø8.0 c/20 C=315 (2ø2c+2ø3c)

2 N7 Ø8.0 C=543 (1c)

2 N11 ø8.0 C=563 (1c)

1 N8 ø8.0 C=117 (2c)

1 N8 ø8.0 C=117 (2c)

15 x 35 247.5

SEÇÃO A-A

28 N1 ø5.0 C=79

1 N8 ø8.0 C=117 (2c)

**V3** ESC 1:50


1 N8 ø8.0 C=117 (2c)

15 x 35 247.5


14 N1 c/18

**V5** ESC 1:50






2 N11 ø8.0 C=563 (1c)



Relação do aço

28 N1 ø5.0 C=79



ASSINATURAS E APROVAÇÃO LEONARDO SILVEIRA LIMA ENGENHEIRO CIVIL - RNP: 0601581067



MARÇO/2023 PRANCHA:

MARÇO/2023 2 / 3

ESCALA:
INDICADA CONTROLE:

ARACATI-CE

CAMILY VASCONCELOS